

HM-2X100A 规格书(交流电源滤波器)


◆ 技术参数 Specification

额定电压 Rated voltage	220VAC
工作频率 Operating frequency	60Hz
额定电流 Rated current	100A
气候类别 Climatic category	25/085/21
漏电流 Leakage current	$\leq 100\text{mA}@220\text{V}/60\text{Hz}$

试验电压 Test voltage (2s/1Min)

线一线 Line-to-line:	1000VDC
线一壳 Line-to-case:	1000VDC

◆ 外形尺寸 Dimension



◆ 特点与应用 Features & Applications

工作频带宽，插入损耗高: Wide operating band, high insert loss

干扰抑制能力强: Strong ability for restrain interference

低压降，低漏电流: Low voltage drop , low leakage current

用于电磁屏蔽房、屏蔽柜、电子方舱、信息安全保密房、医院 CT、核磁共振房、可控硅变流设备、电源净化设备的电源端的滤波 Use for filter in electro-magnetic shielding room、shielding cabinet、electronic、square cabin、information security room 、CT equipment of hospital、nuclear-magnetic、resonance room、SCR current converting equipment、power terminal of the equipments for power purification.

典型插入损耗 Typical insertion loss

频率 Frequency	14K-18GHz
插入损耗 (dB) Insertion loss (dB)	$\geq 100\text{dB}$
共模 Common mode	